

ELECTRONIC SAFETY AND SECURITY SYMBOLS



PUSH BUTTON; LETTER INDICATES AS FOLLOWS:

M=MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T=TECHNOLOGY/TYPE

B-BELL PUSH D-DURESS P-PANIC R-DOOR RELEASE
 X-REQUEST-FOR-EXIT



RECORDER; LETTER INDICATES AS FOLLOWS:

M=MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T=TECHNOLOGY/TYPE

A-AUDIO D-DIGITAL V-VIDEO




SECURITY ACCESS, ANNUNCIATOR PANEL



SECURITY ACCESS, BUZZER. MTD 1'-6" [457mm] AFF UNLESS OTHERWISE NOTED



SECURITY ACCESS, CONTROL UNIT WITH CLOSED CIRCUIT TELEVISION CAMERA



SECURITY ACCESS, GENERIC "X" INDICATES THE TYPE, PROVIDE SCHEDULE OR LEGEND



SECURITY ACCESS, HORN OR SIREN



SECURITY ACCESS, OUTDOOR MICROWAVE TRANSMISSION UNIT



SECURITY ACCESS, PANIC ALARM




SECURITY ACCESS, VIDEO CAMERA WITH LENS

M = MOTION DETECTOR

PZ = MOTION DETECTOR WITH PAN AND ZOOM

PTZ= MOTION DETECTOR WITH PAN, TILT, AND ZOOM



SECURITY ACCESS, PANNING CAMERA TRAVERSE ANGLE



SECURITY ACCESS, VIDEO CAMERA WITH LENS, ANGLE OF VIEW



SECURITY ACCESS, VOLUMETRIC SENSOR



Department of
Veterans Affairs

DETAIL TITLE / ELECTRONIC SAFETY AND SECURITY SYMBOLS

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD280511-09.DWG