

ELECTRONIC SAFETY AND SECURITY SYMBOLS



GLASS BREAKAGE SENSOR; LETTER INDICATES AS FOLLOWS:

M= MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T= TECHNOLOGY/TYPE

A-AUDIO S-SHOCK



INTERCOM; LETTER INDICATES AS FOLLOWS:

M= MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T= TECHNOLOGY/TYPE

M-MASTER S-SUBSTATION



KEYBOARD



KEYPAD DEVICE; LETTER INDICATES AS FOLLOWS:

M= MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL



MONITOR; LETTER INDICATES AS FOLLOWS:

M= MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T= TECHNOLOGY/TYPE

D-DATA G-GRAPHIC M-MULTISCREEN V-VIDEO



MOTION DETECTOR; LETTER INDICATES AS FOLLOWS:

M= MOUNT

C-CEILING D-DESK F-FLUSH H-HIDDEN M-MULLION
 P-PEDESTAL R-RACK S-SURFACE W-WALL

T= TECHNOLOGY/TYPE

D-DUAL TECHNOLOGY IR-INFRARED M-MICROWAVE U-ULTRASONIC
 X-REQUEST-FOR-EXIT



Department of
Veterans Affairs

DETAIL TITLE / ELECTRONIC SAFETY AND SECURITY SYMBOLS

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD280511-08.DWG