

# ELECTRONIC SAFETY AND SECURITY SYMBOLS

R/T



DETECTOR, HEAT; LETTER INDICATES AS FOLLOWS:

R/T = COMBINATION

F = FIXED TEMPERATURE RISE

R/C = RATE COMPENSATION

R = RATE OF



DETECTOR; LETTER INDICATES AS FOLLOWS:

BLANK = SMOKE DETECTOR

H = HEAT SMOKE

I = IONIZATION SMOKE

P = PHOTOELECTRIC SMOKE

IH = IONIZATION AND HEAT SMOKE

IP = IONIZATION AND PHOTOELECTRIC SMOKE

PH = PHOTOELECTRIC AND HEAT SMOKE

IPH = IONIZATION, PHOTOELECTRIC, AND HEAT



DETECTOR, SMOKE, FOR DUCT



DETECTOR, SWITCH LEVEL



FIRE ALARM STATION, MANUAL PULL

—FA—

FIRE ALARM LINE = FA



ELECTROMAGNETIC TYPE DOOR HOLDER OUTLET



CITY FIRE ALARM MASTER STATION MTD 5'-6" [1676mm] AFF UNLESS NOTED.



2-4-6

FIRE ALARM TRANSMITTER (BASE LOOP) NUMERALS DENOTE CODE.



2-4-6

FIRE ALARM TROUBLE TRANSMITTER (BASE LOOP) NUMERALS DENOTE CODE.



Department of  
Veterans Affairs

DETAIL TITLE / ELECTRONIC SAFETY AND SECURITY SYMBOLS

SCALE :NONE

DATE ISSUED: DECEMBER 2008

CAD DETAIL NO.: SD280511-12.DWG